

Stainless Steel Tubing & Fittings

World Leader Since 1976



Valex has led the industry for decades, developing innovative piping products to meet the needs of our customers' ultra-high purity gas systems.

Our market is global, and so is Valex, with factories in the USA and Korea. We produce the widest range of piping components of any supplier. Valex products meet the diverse and exacting standards of all customers from the Silicon Valley of California, to the High Tech Parks of Singapore, Korea, Taiwan, and China.

Benefit from world leadership - choose Valex.



Table of Contents

VALEX Product Lines

Summary of Applications, Materials & Processes2

DIMENSIONS (ASTM)

Tubing and Corresponding Fittings4

Coaxial Tubing and Corresponding Fittings6

SPECIFICATIONS for Ordering (ASTM)

501 UHP Electropolished Tubing.....10

501 UHP Electropolished Fittings.....11

401 UHP Electropolished Tubing.....12

401 UHP Electropolished Fittings.....13

301 HP Electropolished Tubing & Fittings.....14

201 Non-Electropolished Tubing & Fittings.....15

101 Non-Electropolished Tubing & Fittings.....16

222 Hastelloy® C-22® Tubing & Fittings.....17

DIMENSIONS (JIS)

Pipe and Corresponding Fittings18

SPECIFICATIONS for Ordering (JIS)

401 UHP Electropolished Pipe23

401 UHP Electropolished Fittings.....24

201 Non-Electropolished Pipe25


201 Non-Electropolished Fittings.....26

101 Non-Electropolished Pipe27

101 Non-Electropolished Fittings.....28

TERMS & CONDITIONS29

Summary of Applications, Materials & Processes



I.D. SURFACE FINISH (Ra)¹**SIZES¹****VALEX PROCESSES, TESTING, INSPECTION,
CERTIFICATION, MARKING, AND PACKAGING**

5, 7 and 10 μ in.
(0.13, 0.18 and 0.25 μ m)

Seamless:
0.25 thru 1.5 in. (6.35 thru 38.1 mm)

Per Specification SP-9232

5, 7 and 10 μ in.
(0.13, 0.18 and 0.25 μ m)

Seamless:
0.125 thru 2.0 in. (3.18 thru 50.8 mm)
8A thru 100A (13.8 thru 114.3 mm)

Welded:
1.0 thru 6.0 in. (25.4 thru 152.4 mm)
8A thru 250A (13.8 thru 267.4 mm)

Per Specification SP-9220

10 μ in. (0.25 μ m)

Seamless:
0.125 thru 2.0 in. (3.18 thru 50.8 mm)

Welded:
0.5 thru 4.0 in. (12.7 thru 101.6 mm)

Per Specification SP-9223

15, 20 and 25 μ in
(0.38, 0.51 and 0.64 μ m)

Seamless:
0.125 thru 2.0 in. (3.18 thru 50.8 mm)
15A thru 100A (21.7 thru 114.3 mm)

Welded:
0.5 thru 6.0 in. (12.7 thru 152.4 mm)
20A thru 350A (27.2 thru 355.6 mm)

Per Specification SP-9206

40 and 200 μ in.
(1.0 and 5.1 μ m)

Seamless:
0.125 thru 2.0 in. (3.18 thru 50.8 mm)
15A thru 100A (114.3 mm)

Welded:
0.5 thru 6.0 in. (12.7 thru 152.4 mm)
20A thru 500A (27.2 thru 508.0 mm)

Per Specification SP-9204

20, 24 μ in and Mill Finish
(0.51, 0.61 μ m and MF)


Seamless:
0.25 thru 1.0 in. (6.35 thru 25.4 mm)

Welded:
0.5 thru 1.0 in. (12.7 thru 25.4 mm)

Per Specification SP-9207

Dimensions (ASTM)

NOTE: All dimensions are in inches.




TUBE

O.D.	Wall	Weight per foot (lbs.)	Maximum Safe Working Pressure*			
			PSI		Bar	
			Seamless	Welded	Seamless	Welded
.125	.028	0.03	7,805	N.A.	538	N.A.
.250	.035	0.08	4,598	N.A.	317	N.A.
.375	.035	0.13	2,974	N.A.	205	N.A.
.500	.049	0.24	3,136	2,509	216	173
.750	.065	0.48	2,759	2,207	190	152
1.000	.065	0.65	2,039	1,631	141	112
1.500	.065	1.00	1,340	1,072	92	74
2.000	.065	1.35	995	796	69	55
3.000	.065	2.05	N.A.	528	N.A.	36
4.000	.083	3.49	N.A.	505	N.A.	35
6.000	.109	6.90	N.A.	440	N.A.	30


* Maximum safe working pressure is calculated per ASME B31.3-2002, 304.1.2
Material: T304L or T316L per ASTM A269 and A632
Temperature Range = -20°F to +300°F; -28.8°C to +148.9°C

90° ELBOW




O.D.	Wall	A	R
.250	.035	2.06	0.56
.375	.035	2.62	0.56
.500	.049	2.62	0.75
.750	.065	2.62	1.12
1.000	.065	4.00	1.50
1.500	.065	4.75	2.25
2.000	.065	5.50	3.00
3.000	.065	10.00	4.50
4.000	.083	11.00	6.00
6.000	.109	14.00	9.00

45° ELBOW




O.D.	Wall	A	R
.250	.035	1.10	0.56
.375	.035	2.00	0.56
.500	.049	2.50	0.75
.750	.065	2.50	1.12
1.000	.065	3.12	1.50
1.500	.065	3.50	2.25
2.000	.065	3.75	3.00
3.000	.065	6.00	4.50
4.000	.083	7.00	6.00
6.000	.109	8.75	9.00

EQUAL TEE




O.D.	Wall	A	B
.250	.035	1.75	3.50
.375	.035	1.75	3.50
.500	.049	2.12	4.25
.750	.065	2.12	4.25
1.000	.065	2.50	5.00
1.500	.065	2.75	5.50
2.000	.065	3.25	6.50
3.000	.065	5.50	11.00
4.000	.083	6.00	12.00
6.000	.109	10.63	21.25



REDUCING TEE


O.D.	Wall	x	O.D.	Wall	A	B
.375	.035	x	.250	0.35	1.75	3.50
.500	.049	x	.250 - .375	0.35	2.12	4.25
.750	.065	x	.250 - .500	.035 - .049	2.12	4.25
1.00	.065	x	.250 - .750	.035 - .065	2.50	5.00
1.50	.065	x	.250 - 1.00	.035 - .065	2.75	5.50
2.00	.065	x	.250 - 1.50	.035 - .065	3.25	6.50
3.00	.065	x	.250 - 2.00	.035 - .065	3.75	7.50
4.00	.083	x	.250 - 2.00	.035 - .065	4.25	8.50
4.00	.083	x	3.00	.065	6.00	12.00
6.00	.109	x	.250 - 2.00	.035 - .065	6.00	12.00
6.00	.109	x	3.00 - 4.00	.065 - .083	11.00	22.00



CONCENTRIC REDUCER

O.D.	Wall	x	O.D.	Wall	A
.375	.035	x	.250	.035	2.75
.500	.049	x	.250 - .375	.035	2.75
.750	.065	x	.250 - .500	.035 - .049	2.75
1.00	.065	x	.250 - .750	.035 - .065	3.00
1.50	.065	x	.250 - 1.00	.035 - .065	5.25
2.00	.065	x	.250 - 1.50	.035 - .065	5.50
3.00	.065	x	.500 - 2.00	.049 - .065	6.00
4.00	.083	x	.750 - 3.00	.065	6.50
6.00	.109	x	1.00 - 4.00	.065 - .083	11.50


SIZES OTHER THAN SHOWN MAY BE AVAILABLE FROM FACTORY



END CAP

O.D.	Wall	A
.250	.035	1.125
.375	.035	1.125
.500	.049	1.375
.750	.065	1.75
1.000	.065	1.75
1.500	.065	2.00
2.000	.065	2.00
3.000	.065	2.00
4.000	.083	2.50
6.000	.109	4.77


Dimensions (ASTM)



COAXIAL TUBE


Size		Weight per foot (lbs)	Maximum Safe Working Pressure *	
Inner	Outer		PSI	Bar
.250 x .035	.500 x .049	0.32	3,136	216
.375 x .035	.625 x .049	0.43	2,477	171
.500 x .049	.750 x .065	0.71	2,759	190
.750 x .065	1.00 x .065	1.13	1,631	112
1.00 x .065	1.25 x .065	1.48	1,294	89
1.50 x .065	2.00 x .065	2.35	796	55

* Maximum safe working pressure is calculated for the outer jacket per ASME B31.3-2002, 304.1.2 (304L/316L, -20°F to 300°F). Weight includes inner and outer tube.




COAXIAL 90° ELBOW

Inner Tube O.D.	Inner Tube Wall	Outer Tube O.D.	Outer Tube Wall	A	B
.250	.035	.500	.049	1.00	4.37
.375	.035	.625	.049	1.00	4.12
.500	.049	.750	.065	1.00	4.25
.750	.065	1.00	.065	1.75	6.75
1.00	.065	1.25	.065	1.75	7.12
1.50	.065	2.00	.065	2.00	8.37




COAXIAL 45° ELBOW

Inner Tube O.D.	Inner Tube Wall	Outer Tube O.D.	Outer Tube Wall	A	B
.250	.035	.500	.049	1.00	4.00
.375	.035	.625	.049	1.00	3.87
.500	.049	.750	.065	1.00	3.87
.750	.065	1.00	.065	1.75	6.12
1.00	.065	1.25	.065	1.75	6.25
1.50	.065	2.00	.065	2.00	7.12




COAXIAL EQUAL TEE

Inner Tube O.D.	Inner Tube Wall	Outer Tube O.D.	Outer Tube Wall	A	B	C
.250	.035	.500	.049	1.00	3.87	7.75
.375	.035	.625	.049	1.00	4.00	8.00
.500	.049	.750	.065	1.00	4.00	8.00
.750	.065	1.00	.065	1.75	6.37	12.75
1.00	.065	1.25	.065	1.75	6.50	13.00
1.50	.065	2.00	.065	2.00	7.62	15.25




COAXIAL REDUCING TEE

Inner Tube O.D.	Inner Tube Wall	x	Inner Tube O.D.	Inner Tube Wall	Outer Tube O.D.	Outer Tube Wall	x	Outer Tube O.D.	Outer Tube Wall	A	B	C	D	E
.375	.035	x	.250	.035	.625	.049	x	.500	.049	1.00	3.87	7.75	1.00	4.12
.500	.049	x	.250	.035	.750	.065	x	.500	.049	1.00	3.87	7.75	1.00	4.12
.500	.049	x	.375	.035	.750	.065	x	.625	.049	1.00	4.00	8.00	1.00	4.12
.750	.065	x	.250	.035	1.000	.065	x	.500	.049	1.75	6.12	12.25	1.00	4.25
.750	.065	x	.375	.035	1.000	.065	x	.625	.049	1.75	6.25	12.50	1.00	4.25
.750	.065	x	.500	.049	1.000	.065	x	.750	.065	1.75	6.25	12.50	1.00	4.25
1.000	.065	x	.250	.035	1.250	.065	x	.500	.049	1.75	6.12	12.25	1.00	4.37
1.000	.065	x	.375	.035	1.250	.065	x	.625	.049	1.75	6.25	12.50	1.00	4.37
1.000	.065	x	.500	.049	1.250	.065	x	.750	.065	1.75	6.25	12.50	1.00	4.37
1.000	.065	x	.750	.065	1.250	.065	x	1.000	.065	1.75	6.37	12.75	1.75	6.62
1.500	.065	x	.750	.065	2.000	.065	x	1.000	.065	2.00	7.12	14.25	1.75	7.00
1.500	.065	x	1.000	.065	2.000	.065	x	1.250	.065	2.00	7.25	14.50	1.75	7.00



COAXIAL CONCENTRIC REDUCER


Inner Tube O.D.	Inner Tube Wall	x	Inner Tube O.D.	Inner Tube Wall	Outer Tube O.D.	Outer Tube Wall	x	Outer Tube O.D.	Outer Tube Wall	A	B
.375	.035	x	.250	.035	.625	.049	x	.500	.049	4.00	4.00
.500	.049	x	.250	.035	.750	.065	x	.500	.049	4.00	4.00
.500	.049	x	.375	.035	.750	.065	x	.625	.049	4.00	4.00
.750	.065	x	.250	.035	1.000	.065	x	.500	.049	5.00	5.75
.750	.065	x	.375	.035	1.000	.065	x	.625	.049	5.00	5.75
.750	.065	x	.500	.049	1.000	.065	x	.750	.065	5.00	5.75
1.000	.065	x	.250	.035	1.250	.065	x	.500	.049	5.00	5.75
1.000	.065	x	.375	.035	1.250	.065	x	.625	.049	5.00	5.75
1.000	.065	x	.500	.049	1.250	.065	x	.750	.065	5.00	5.75
1.000	.065	x	.750	.065	1.250	.065	x	1.000	.065	6.50	6.50
1.500	.065	x	.250	.035	2.000	.065	x	.500	.049	5.75	6.75
1.500	.065	x	.375	.035	2.000	.065	x	.625	.049	5.75	6.75
1.500	.065	x	.500	.049	2.000	.065	x	.750	.065	5.75	6.75
1.500	.065	x	.750	.065	2.000	.065	x	1.000	.065	7.25	7.50
1.500	.065	x	1.000	.065	2.000	.065	x	1.250	.065	7.25	7.50



COAXIAL PURGE TEE


Size	Outer Tube O.D.	Outer Tube Wall	A	B	C	F5
.250	.500	.049	2.87	5.75	1.51	.25
.375	.625	.049	3.00	6.00	1.57	.25
.500	.750	.065	3.00	6.00	1.62	.25
.750	1.000	.065	4.62	9.25	1.74	.25
1.00	1.250	.065	4.75	9.50	1.87	.25
1.50	2.000	.065	5.62	11.25	2.25	.25

Dimensions (ASTM)



COAXIAL PURGE TEE WITH FACE SEAL GLAND


Inner Tube O.D.	Inner Tube Wall	Outer Tube O.D.	Outer Tube Wall	A	B	C	D	FS ₁	FS ₂
.250	.035	.500	.049	1.00	3.87	7.75	1.51	.25	.25
.375	.035	.625	.049	1.00	4.00	8.00	1.57	.25	.37
.500	.049	.750	.065	1.00	4.00	8.00	1.62	.25	.50



COAXIAL SLEEVE


Size	A	B	C	C (E4*)	C (E5*)	C (E6*)
.250	.505/.509	.62	2.50	4.00	5.00	6.00
.375	.630/.634	.75	2.50	4.00	5.00	6.00
.500	.756/.760	.87	2.50	4.00	5.00	6.00
.750	1.006/1.010	1.12	4.00	N.A.	5.00	6.00
1.00	1.256/1.260	1.37	4.00	N.A.	N.A.	N.A.
1.50	2.021/2.025	2.12	4.50	N.A.	N.A.	N.A.

* Extra length




COAXIAL FEMALE FACE SEAL WELD GLAND

Size	A	B	FS
.250	3.50	1.00	.250
.375	3.50	1.00	.375
.500	3.50	1.00	.500




COAXIAL MALE FACE SEAL WELD GLAND

Size	A	B	FS
.250	3.50	1.00	.250
.375	3.50	1.00	.375
.500	3.50	1.00	.500



COAXIAL TERMINATOR

Size	A	B	C
.250	.500	3.25	1.250
.375	.625	.450	1.250
.500	.750	.603	1.250
.750	1.000	.885	2.000
1.000	1.250	1.135	2.000
1.500	2.000	1.870	2.250



COAXIAL BULKHEAD FITTING ASSEMBLY

Size	A	B	C	Hex Nut Size
.250	.500	1.00	3.625	3/4" - 16UNF
.375	.625	1.00	3.625	7/8" - 14UNF
.500	.750	1.00	3.625	1-1/16" - 12UNF
.750	1.000	1.75	5.125	1-5/16" - 12UNF
1.000	1.250	1.75	5.125	1-5/8" - 12UNF

FITTINGS

PART NO.		G		-		.		X		.		-			

NOTE: Not all configurations are available. Part number options may be subject to change. Please refer to SP-9200 at www.valex.com for the latest revision.

* For use only with Reducing Tees and Concentric Reducers - specify reduced tube size. Example for Reducing Tee:

G 7 R - . 5 X . 3 7 5 - A 5

COAXIAL FITTINGS

PART NO.		F						-	.					X		.					-		
Type																							
2	90° Elbow																						
2K	45° Elbow																						
7	Equal Tee																						
7R	Reducing Tee																						
31	Concentric Reducer																						
7PFS	Purge Tee with FS																						
14FS	FS Weld Gland, Female																						
15FS	FS Weld Gland, Male																						
Size (O.D.) Specify Process (Inner) Tube Size																							
.25	1/4" O.D. x .035" inner tube (6.35 x 0.89mm) with 1/2" O.D. x .049" outer tube (12.7 x 1.24mm)																						
.375	3/8" O.D. x .035" inner tube (9.53 x 0.89mm) with 5/8" O.D. x .049" outer tube (15.87 x 1.24mm)																						
.5	1/2" O.D. x .049" inner tube (12.7 x 1.24mm) with 3/4" O.D. x .065" outer tube (19.05 x 1.65mm)																						
Visual Characteristics																							
A	Surface conditions (allowable number and severity of flaws) are coded A and B with A being superior. Each surface code is defined by a set of workmanship standards that are configuration and change controlled.																						
B																							
Surface Roughness																							
5	5Ra µin max																						
7	7Ra µin max																						
0	For "B" above, 10Ra µin max																						

NOTE: Not all configurations are available. Part number options may be subject to change. Please refer to SP-9200 at www.valex.com for the latest revision.

* For use only with Reducing Tees and Concentric Reducers - specify reduced tube size. Example for Reducing Tee:

F 7 R - . 5 X . 2 5 - A 5

FITTINGS

E OS/OW (Single-melt 316L)
Q VS (Double-melt 316L seamless)
RE RS/RW (Single-melt 316L)
Y KS (Double-melt 316L seamless)

Type
2 90° Elbow
2W 90° Elbow, welded
2K 45° Elbow
2KW 45° Elbow, welded
7 Equal Tee
7W Equal Tee, welded
7R Reducing Tee
7RW Reducing Tee, welded x seamless
7RWW Reducing Tee, welded x welded
16 End Cap
16W End Cap, welded
31 Concentric Reducer
31W Concentric Reducer, welded x seamless
31WW Concentric Reducer, welded x welded

Size (O.D.)
.25 1/4" O.D. x .035" wall (6.35 x 0.89mm)
.375 3/8" O.D. x .035" wall (9.53 x 0.89mm)
.5 1/2" O.D. x .049" wall (12.7 x 1.24mm)
.75 3/4" O.D. x .065" wall (19.05 x 1.65mm)
1 1" O.D. x .065" wall (25.4 x 1.65mm)
1.5 1.5" O.D. x .065" wall (38.1 x 1.65mm)
2 2" O.D. x .065" wall (50.8 x 1.65mm)
3 3" O.D. x .065" wall (76.2 x 1.65mm)
4 4" O.D. x .083" wall (101.6 x 2.1mm)
6 6" O.D. x .109" wall (152.4 x 2.76mm)

Visual Characteristics

A Surface conditions (allowable number and severity of flaws) are coded A, B and C with A being superior. Each surface code is defined by a set of workmanship standards that are configuration and change controlled.

Surface Roughness

5 5Ra µin max
7 7Ra µin max
0 For "B" above, 10Ra µin max; for "C" above, 10Ra µin

NOTE: Not all configurations are available. Part number options may be subject to change. Please refer to SP-9200 at www.valex.com for the latest revision.

* For use only with Reducing Tees and Concentric Reducers - specify reduced tube size. Example for Reducing Tee.

E 7 R - 1 X . 3 7 5 - A 7

COAXIAL FITTINGS

PART NO.

Inner Alloy (Per Valex SP-9200)
C OS/OW (Single-melt 316L)
R VS (Double-melt 316L seamless)
RC RS/RW (Single-melt 316L)
W KS (Double-melt 316L seamless)

Type
2 90° Elbow
2K 45° Elbow
7 Equal Tee
7R Reducing Tee
31 Concentric Reducer
7P Purge Tee
7PFS Purge Tee with FS
12 Sleeve
14FS FS Weld Gland, Female
15FS FS Weld Gland, Male
16 Terminator
17BH Bulkhead Fitting

Size (O.D.) Specify Process (Inner) Tube Size
.25 1/4" O.D. x .035" inner tube (6.35 x 0.89mm) with 1/2" O.D. x .049" outer tube (12.7 x 1.24mm)
.375 3/8" O.D. x .035" inner tube (9.53 x 0.89mm) with 5/8" O.D. x .049" outer tube (15.87 x 1.24mm)
.5 1/2" O.D. x .049" inner tube (12.7 x 1.24mm) with 3/4" O.D. x .065" outer tube (19.05 x 1.65mm)
.75 3/4" O.D. x .065" inner tube (19.05 x 1.65mm) with 1" O.D. x .065" outer tube (25.4 x 1.65mm)
1 1" O.D. x .065" inner tube (25.4 x 1.65mm) with 1.25" O.D. x .065" outer tube (31.75 x 1.65mm)
1.5 1.5" O.D. x .065" inner tube (38.1 x 1.65mm) with 2" O.D. x .065" outer tube (50.8 x 1.65mm)

Visual Characteristics

A Surface conditions (allowable number and severity of flaws) are coded A and B with A being superior. Each surface code is defined by a set of workmanship standards that are configuration and change controlled.

Surface Roughness

5 5Ra µin max
7 7Ra µin max
0 For "B" above, 10Ra µin max; for "C" above, 10Ra µin

NOTE: Not all configurations are available. Part number options may be subject to change. Please refer to SP-9200 at www.valex.com for the latest revision.

* For use only with Reducing Tees and Concentric Reducers - specify reduced tube size. Example for Reducing Tee.

C 7 R - . 5 X . 2 5 - A 7

Specification 301 HP Electropolished (ASTM)

TUBE

PART NO. - - -

Process

T3A Tube, Valex 301 Specification

Alloy (Per Valex SP-9200)

OS Single-melt 316L seamless

OW Single-melt 316L welded

Size (O.D.)

00125 1/8" (3.18mm), 10' length

00250 1/4" (6.35mm), 20' length

00375 3/8" (9.53mm), 20' length

00500 1/2" (12.7mm), 20' length

00750 3/4" (19.05mm), 20' length

01000 1" (25.4mm), 20' length

01500 1.5" (38.1mm), 20' length

02000 2" (50.8mm), 20' length

03000 3" (76.2mm), 20' length

04000 4" (101.6mm), 20' length

Wall Thickness

028 .028" (0.71mm)

035 .035" (0.89mm)

049 .049" (1.24mm)

065 .065" (1.65mm)

083 .083" (2.10mm)

NOTE: Not all configurations are available. Part number options may be subject to change. Please refer to SP-9200 at www.valex.com for the latest revision.

Example: T3A - OS - 00500 - 049

FITTINGS

PART NO. L - X

Type

2 90° Elbow

2W 90° Elbow, welded

2K 45° Elbow

2KW 45° Elbow, welded

7 Equal Tee

7W Equal Tee, welded

7R Reducing Tee

7RW Reducing Tee, welded x seamless

7RWW Reducing Tee, welded x welded

16 End Cap

16W End Cap, welded

31 Concentric Reducer

31W Concentric Reducer, welded x seamless

31WW Concentric Reducer, welded x welded

Size (O.D.)

.25 1/4" O.D. x .035" wall (6.35 x 0.89mm)

.375 3/8" O.D. x .035" wall (9.53 x 0.89mm)

.5 1/2" O.D. x .049" wall (12.7 x 1.24mm)

.75 3/4" O.D. x .065" wall (19.05 x 1.65mm)

1 1" O.D. x .065" wall (25.4 x 1.65mm)

1.5 1.5" O.D. x .065" wall (38.1 x 1.65mm)

2 2" O.D. x .065" wall (50.8 x 1.65mm)

3 3" O.D. x .065" wall (76.2 x 1.65mm)

4 4" O.D. x .083" wall (101.6 x 2.1mm)

NOTE: Not all configurations are available. Part number options may be subject to change. Please refer to SP-9200 at www.valex.com for the latest revision.

* For use only with Reducing Tees and Concentric Reducers - specify reduced tube size. Example for Reducing Tee:

L7RW - 1 X .375

Dimensions (JIS)

NOTE: All dimensions are in millimeters.


PIPE


Size	Sch.	O.D.	Wall	Weight per meter (kg)	Maximum Safe Working Pressure*			
					Bar		PSI	
					Seamless	Welded	Seamless	Welded
8A	5S	13.8	1.2	0.38	171	136	2,474	1,979
10A	5S	17.3	1.2	0.48	135	108	1,959	1,567
15A	5S	21.7	1.65	0.82	158	126	2,291	1,833
20A	5S	27.2	1.65	1.05	125	100	1,813	1,451
25A	5S	34.0	1.65	1.32	99	79	1,440	1,152
32A	5S	42.7	1.65	1.68	78	63	1,138	911
40A	5S	48.6	1.65	1.92	69	55	997	797
50A	5S	60.5	1.65	2.41	55	44	797	638
65A	5S	76.3	2.1	3.87	57	46	824	660
80A	5S	89.1	2.1	4.53	49	39	704	563
90A	5S	101.6	2.1	5.19	42	34	616	493
100A	5S	114.3	2.1	5.85	38	30	547	437
125A	5S	139.8	2.8	9.52	41	33	597	477
150A	5S	165.2	2.8	11.29	35	28	504	403
200A	5S	216.3	2.8	14.84	26	21	384	307
250A	5S	267.4	3.4	22.28	26	21	377	302
300A	5S	318.5	4.0	31.22	26	21	372	298
8A	10S	13.8	1.65	0.50	254	204	3,689	2,951
10A	10S	17.3	1.65	0.64	200	160	2,904	2,323
15A	10S	21.7	2.1	1.02	210	168	3,038	2,431
20A	10S	27.2	2.1	1.31	165	132	2,396	1,917
25A	10S	34.0	2.8	2.17	177	142	2,568	2,054
32A	10S	42.7	2.8	2.77	139	111	2,019	1,616
40A	10S	48.6	2.8	3.18	122	97	1,764	1,411
50A	10S	60.5	2.8	4.01	97	78	1,405	1,124
65A	10S	76.3	3.0	5.46	82	66	1,188	950
80A	10S	89.1	3.0	6.41	70	56	1,013	810
90A	10S	101.6	3.0	7.34	61	49	886	709
100A	10S	114.3	3.0	8.29	54	43	786	628
125A	10S	139.8	3.4	11.51	50	40	727	582
150A	10S	165.2	3.4	13.65	42	34	613	491
200A	10S	216.3	4.0	21.08	38	30	550	440
250A	10S	267.4	4.0	26.15	31	24	444	355
300A	10S	318.5	4.5	35.07	29	23	419	335
350A	N.A.	355.6	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
400A	N.A.	406.4	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.

* Maximum safe working pressure is calculated per ASME B31.3-2002, 304.1.2

Material: T304L or T316L per JIS G3459


Temperature Range = -28.8°C to +148.9°C, -20°F to +300°F






90° ELBOW (LONG)

Size	O.D.	Wall		A	R
		5S	10S		
8A	13.8	1.2	1.65	55	25.4
10A	17.3	1.2	1.65	62	25.4
15A	21.7	1.65	2.1	75	38.1
20A	27.2	1.65	2.1	75	38.1
25A	34.0	1.65	2.8	75	38.1
32A	42.7	1.65	2.8	94	47.6
40A	48.6	1.65	2.8	104	57.2
50A	60.5	1.65	2.8	123	76.2
65A	76.3	2.1	3.0	147	95.3
80A	89.1	2.1	3.0	166	114.3
100A	114.3	2.1	3.0	204	152.4
125A	139.8	2.8	3.4	250	190.5
150A	165.2	2.8	3.4	290	228.6
200A	216.3	2.8	4.0	375	304.8



90° ELBOW (SHORT)


Size	O.D.	Wall		A	R
		5S	10S		
8A	13.8	1.2	1.65	42	12.7
10A	17.3	1.2	1.65	49	12.7
15A	21.7	1.65	2.1	49	12.7
20A	27.2	1.65	2.1	56	19.1
25A	34.0	1.65	2.8	62	25.4
32A	42.7	1.65	2.8	78	31.8
40A	48.6	1.65	2.8	85	38.1
50A	60.5	1.65	2.8	97	50.8
65A	76.3	2.1	3.0	115	63.5
80A	89.1	2.1	3.0	128	76.2
100A	114.3	2.1	3.0	153	101.6
125A	139.8	2.8	3.4	185	127.0
150A	165.2	2.8	3.4	210	152.4
200A	216.3	2.8	4.0	275	203.2



45° ELBOW

Size	O.D.	Wall		A	R
		5S	10S		
8A	13.8	1.2	1.65	40	25.4
10A	17.3	1.2	1.65	47	25.4
15A	21.7	1.65	2.1	52	38.1
20A	27.2	1.65	2.1	52	38.1
25A	34.0	1.65	2.8	52	38.1
32A	42.7	1.65	2.8	66	47.6
40A	48.6	1.65	2.8	70	57.2
50A	60.5	1.65	2.8	78	76.2
65A	76.3	2.1	3.0	91	95.3
80A	89.1	2.1	3.0	99	114.3
100A	114.3	2.1	3.0	115	152.4
125A	139.8	2.8	3.4	145	190.5
150A	165.2	2.8	3.4	155	228.6
200A	216.3	2.8	4.0	195	304.8

NOTE: For sizes 250A and larger please contact Valex for availability.




EQUAL TEE

Size	O.D.	Wall		A	B
		5S	10S		
8A	13.8	1.2	1.65	42	84
10A	17.3	1.2	1.65	49	98
15A	21.7	1.65	2.1	59	118
20A	27.2	1.65	2.1	65	130
25A	34.0	1.65	2.8	68	136
32A	42.7	1.65	2.8	88	176
40A	48.6	1.65	2.8	95	190
50A	60.5	1.65	2.8	102	204
65A	76.3	2.1	3.0	121	242
80A	89.1	2.1	3.0	130	260
100A	114.3	2.1	3.0	145	290
125A	139.8	2.8	3.4	160	320
150A	165.2	2.8	3.4	170	340
200A	216.3	2.8	4.0	190	380

NOTE: For sizes 250A and larger please contact Valex for availability.

REDUCING TEE


Size	O.D.	Wall		X	Size	O.D.	Wall		A	B	C
		5S	10S				5S	10S			
10A	17.3	1.2	1.65	x	8A	13.8	1.2	1.65	47	44	94
15A	21.7	1.65	2.1	x	8A	13.8	1.2	1.65	47	44	94
15A	21.7	1.65	2.1	x	10A	17.3	1.2	1.65	52	52	104
20A	27.2	1.65	2.1	x	8A	13.8	1.2	1.65	47	47	94
20A	27.2	1.65	2.1	x	10A - 15A	17.3 - 21.7	1.2 - 1.65	1.65 - 2.1	55	55	110
25A	34.0	1.65	2.8	x	8A	13.8	1.2	1.65	47	50	94
25A	34.0	1.65	2.8	x	10A - 20A	17.3 - 27.2	1.2 - 1.65	1.65 - 2.1	59	59	118
32A	42.7	1.65	2.8	x	8A	13.8	1.2	1.65	57	54	114
32A	42.7	1.65	2.8	x	10A - 25A	17.3 - 34.0	1.2 - 1.65	1.65 - 2.8	68	62	136
40A	48.6	1.65	2.8	x	8A	13.8	1.2	1.65	57	57	114
40A	48.6	1.65	2.8	x	10A - 25A	17.3 - 34.0	1.2 - 1.65	1.65 - 2.8	68	65	136
40A	48.6	1.65	2.8	x	32A	42.7	1.65	2.8	77	77	154
50A	60.5	1.65	2.8	x	8A	13.8	1.2	1.65	57	63	114
50A	60.5	1.65	2.8	x	10A - 25A	17.3 - 34.0	1.2 - 1.65	1.65 - 2.8	68	71	136
50A	60.5	1.65	2.8	x	32A - 40A	42.7 - 48.6	1.65	2.8	83	83	166
65A	76.3	2.1	3.0	x	8A	13.8	1.2	1.65	61	71	122
65A	76.3	2.1	3.0	x	10A - 25A	17.3 - 34.0	1.2 - 1.65	1.65 - 2.8	72	79	144
65A	76.3	2.1	3.0	x	32A - 50A	42.7 - 60.5	1.65	2.8	88	90	176
80A	89.1	2.1	3.0	x	8A	13.8	1.2	1.65	61	77	122
80A	89.1	2.1	3.0	x	10A - 25A	17.3 - 34.0	1.2 - 1.65	1.65 - 2.8	72	85	144
80A	89.1	2.1	3.0	x	32A - 50A	42.7 - 60.5	1.65	2.8	88	96	176
80A	89.1	2.1	3.0	x	65A	76.3	2.1	3.0	103	103	206
100A	114.3	2.1	3.0	x	8A	13.8	1.2	1.65	61	90	122
100A	114.3	2.1	3.0	x	10A - 25A	17.3 - 34.0	1.2 - 1.65	1.65 - 2.8	72	98	144
100A	114.3	2.1	3.0	x	32A - 50A	42.7 - 60.5	1.65	2.8	88	109	176
100A	114.3	2.1	3.0	x	65A - 80A	76.3 - 89.1	2.1	3.0	116	116	232
125A	139.8	2.8	3.4	x	8A	13.8	1.2	1.65	80	110	160
125A	139.8	2.8	3.4	x	10A - 25A	17.3 - 34.0	1.2 - 1.65	1.65 - 2.8	100	120	200
125A	139.8	2.8	3.4	x	32A - 50A	42.7 - 60.5	1.65	2.8	120	130	240
125A	139.8	2.8	3.4	x	65A - 100A	76.3 - 114.3	2.1	3.0	140	140	280
150A	165.2	2.8	3.4	x	8A	13.8	1.2	1.65	90	130	180
150A	165.2	2.8	3.4	x	10A - 25A	17.3 - 34.0	1.2 - 1.65	1.65 - 2.8	110	140	220
150A	165.2	2.8	3.4	x	32A - 50A	42.7 - 60.5	1.65	2.8	130	150	260
150A	165.2	2.8	3.4	x	65A - 100A	76.3 - 114.3	2.1	3.0	150	160	300
150A	165.2	2.8	3.4	x	125A	139.8	2.8	3.4	170	170	340
200A	216.3	2.8	4.0	x	8A	13.8	1.2	1.65	100	150	200
200A	216.3	2.8	4.0	x	10A - 25A	17.3 - 34.0	1.2 - 1.65	1.65 - 2.8	120	160	240
200A	216.3	2.8	4.0	x	32A - 50A	42.7 - 60.5	1.65	2.8	140	170	280
200A	216.3	2.8	4.0	x	65A - 100A	76.3 - 114.3	2.1	3.0	160	180	320
200A	216.3	2.8	4.0	x	125A - 150A	139.8 - 165.2	2.8	3.4	180	190	360



NOTE: For sizes 250A and larger please contact Valex for availability.

CONCENTRIC REDUCER

Size	O.D.	Wall		X	Size	O.D.	Wall		A
		5S	10S				5S	10S	
10A	17.3	1.2	1.65	x	8A	13.8	1.2	1.65	90
15A	21.7	1.65	2.1	x	8A - 10A	13.8 - 17.3	1.2	1.65	100
20A	27.2	1.65	2.1	x	8A - 15A	13.8 - 21.7	1.2 - 1.65	1.65 - 2.1	105
25A	34.0	1.65	2.8	x	8A - 20A	13.8 - 27.2	1.2 - 1.65	1.65 - 2.1	120
32A	42.7	1.65	2.8	x	8A - 25A	13.8 - 34.0	1.2 - 1.65	1.65 - 2.8	125
40A	48.6	1.65	2.8	x	8A - 32A	13.8 - 42.7	1.2 - 1.65	1.65 - 2.8	130
50A	60.5	1.65	2.8	x	8A - 40A	13.8 - 48.6	1.2 - 1.65	1.65 - 2.8	140
65A	76.3	2.1	3.0	x	8A - 50A	13.8 - 60.5	1.2 - 1.65	1.65 - 2.8	165
80A	89.1	2.1	3.0	x	8A - 65A	13.8 - 76.3	1.2 - 2.1	1.65 - 3.0	170
100A	114.3	2.1	3.0	x	8A - 80A	13.8 - 89.1	1.2 - 2.1	1.65 - 3.0	180
125A	139.8	2.8	3.4	x	8A - 100A	13.8 - 114.3	1.2 - 2.1	1.65 - 3.0	250
150A	165.2	2.8	3.4	x	8A - 125A	13.8 - 139.8	1.2 - 2.8	1.65 - 3.4	260
200A	216.3	2.8	4.0	x	8A - 150A	13.8 - 165.2	1.2 - 2.8	1.65 - 3.4	280



Specification 401 UHP Electropolished (JIS)

FITTINGS

PART NO.

J	E				
---	---	--	--	--	--

 -

--	--	--	--	--	--

 X

--	--	--	--	--	--

 -

--	--	--	--	--	--

Type

2(S)	90° Elbow, short
2(L)	90° Elbow, long
2W(S)	90° Elbow, short, welded
2W(L)	90° Elbow, long, welded
2K	45° Elbow
2KW	45° Elbow, welded
7	Equal Tee
7W	Equal Tee, welded
7R	Reducing Tee
7RW	Reducing Tee, welded x seamless
7RWW	Reducing Tee, welded x welded
31	Concentric Reducer
31W	Concentric Reducer, welded x seamless
31WW	Concentric Reducer, welded x welded

Size (O.D.)

8A	13.8mm
10A	17.3mm
15A	21.7mm
20A	27.2mm
25A	34.0mm
32A	42.7mm
40A	48.6mm
50A	60.5mm
65A	76.3mm
80A	89.1mm
100A	114.3mm
125A	139.8mm
150A	165.2mm
200A	216.3mm
250A	267.4mm

Pipe Schedule

BLANK	JIS Pipe Schedule 5
T	JIS Pipe Schedule 10

Visual Characteristics

A	Surface conditions (allowable number and severity of flaws) are coded A, B, and C with A being superior. Each surface code is defined by a set of workmanship standards that are configured and change controlled.
B	
C	

Surface Roughness

5	5Ra µin max
7	7Ra µin max
0	For "B" above, 10Ra µin max: for "C" above, 10Ra µin

Note: Not all configurations are available. Part number options may be subject to change. Please refer to SP-9200 at www.valex.com for the latest revision

* For use only with Reducing Tees and Concentric Reducers - specify reduced pipe size. Example for Reducing Tee:

J	E	7	R		
---	---	---	---	--	--

 -

8	0	A			
---	---	---	--	--	--

 X

2	0	A			
---	---	---	--	--	--

 -

B					
---	--	--	--	--	--

0

Specification 201 Non-Electropolished (JIS)

PIPE

PART NO.

--	--	--

 -

--	--

 -

--	--	--	--	--

 X4 -

--	--	--

Process

P2A Pipe, Valex 201 Specification

Alloy (Per Valex SP-9200)

2S Single-melt 304L seamless
2W Single-melt 304L welded
AS Single-melt 304 seamless
AW Single-melt 304 welded
RS Single-melt 316L seamless
RW Single-melt 316L welded

Size (O.D.)

0015A 21.7mm, 6M length
0020A 27.2mm, 6M length
0025A 34.0mm, 6M length
0032A 42.7mm, 6M length
0040A 48.6mm, 6M length
0050A 60.5mm, 6M length
0065A 76.3mm, 6M length
0080A 89.1mm, 6M length
0090A 101.6mm, 6M length
0100A 114.3mm, 6M length
0125A 139.8mm, 6M length
0150A 165.2mm, 6M length
0200A 216.3mm, 6M length
0250A 267.4mm, 6M length
0300A 318.5mm, 6M length
0350A 355.6mm, 6M length

* { 015A 21.7mm, 4M length
020A 27.2mm, 4M length
025A 34.0mm, 4M length
032A 42.7mm, 4M length
040A 48.6mm, 4M length
050A 60.5mm, 4M length
065A 76.3mm, 4M length
080A 89.1mm, 4M length
090A 101.6mm, 4M length
100A 114.3mm, 4M length
125A 139.8mm, 4M length
150A 165.2mm, 4M length
200A 216.3mm, 4M length
250A 267.4mm, 4M length
300A 318.5mm, 4M length
350A 355.6mm, 4M length

Pipe Schedule

05S JIS Pipe Schedule 5
10S JIS Pipe Schedule 10
* { 05 JIS Pipe Schedule 5
10 JIS Pipe Schedule 10

Note: Not all configurations are available. Part number options may be subject to change. Please refer to SP-9200 at www.valex.com for the latest revision.

* For use only with 4-meter lengths. Example for 4-meter length pipe:

P	2	A
---	---	---

 -

R	S
---	---

 -

0	2	0	A
---	---	---	---

 X4 -

0	5
---	---

27

PART NO.

P	1	A	-	R	S	-	0	2	0	A		X4	-	0	5	
---	---	---	---	---	---	---	---	---	---	---	--	----	---	---	---	--

Specification 101 Non-Electropolished (JIS)

FITTINGS

PART NO.

J	A				
---	---	--	--	--	--

•

--	--	--	--

1

7

$\times$				
----------	--	--	--	--

*

Type

2(S)	90° Elbow, short
2(L)	90° Elbow, long
2W(S)	90° Elbow, short, welded
2W(L)	90° Elbow, long, welded
2K	45° Elbow
2KW	45° Elbow, welded
7	Equal Tee
7W	Equal Tee, welded
7R	Reducing Tee
7RW	Reducing Tee, welded x seamless
7RWW	Reducing Tee, welded x welded
31	Concentric Reducer
31W	Concentric Reducer, welded x seamless
31WW	Concentric Reducer, welded x welded

Size (O.D.)

15A	21.7mm
20A	27.2mm
25A	34.0mm
32A	42.7mm
40A	48.6mm
50A	60.5mm
65A	76.3mm
80A	89.1mm
100A	114.3mm
125A	139.8mm
150A	165.2mm
200A	216.3mm
250A	267.4mm

Pipe Schedule

BLANK	JIS Pipe Schedule 5
T	JIS Pipe Schedule 10

Note: Not all configurations are available. Part number options may be subject to change. Please refer to SP-9200 at www.valex.com for the latest revision.

* For use only with Reducing Tees and Concentric Reducers - specify reduced pipe size. Example for Reducing Tee:

J	A	7	R		
---	---	---	---	--	--

•

8	0	A	
---	---	---	--

1

1

X	2	0	A	
---	---	---	---	--

STANDARD TERMS & CONDITIONS

CONTROLLING PROVISIONS:

These terms and conditions shall replace all terms and conditions of Buyer's order and of any proposal or quotation to Buyer not agreed to by Buyer and Seller prior to the date of invoice. In the absence of a written acceptance by Buyer, an acceptance of any goods covered by Buyer's order shall constitute an acceptance of these terms and conditions. No waiver, alteration or modification of these provisions shall be valid unless made in writing and signed by an officer or other authorized representative of Seller.

PRICE, QUOTATIONS, & DISCOUNTS:

List prices, discounts, and quotations are subject to change without notice. All orders are subject to acceptance in writing by Seller. If it is necessary to change prices after order acceptance, Buyer's approval will be obtained prior to shipment; otherwise the order will be deemed canceled. **MINIMUM ORDER: \$150.00**

TERMS:

1% cash discount will be allowed on all invoices if paid by check dated and envelope postmarked not later than ten (10) days following date of invoice; otherwise net 30 days. A carrying charge of 1 1/2% per month will be assessed on all overdue accounts.

CANCELLATIONS OR ADD-ONS:

Since all orders are individually entered for processing immediately upon receipt, Seller reserves the right to charge back to the Buyer costs incurred from either cancellation of the order or change of the order or of any item on the order. Seller also reserves the right to consider all add-ons as separate and new orders subject to all terms and conditions.

SHIPMENTS:

Seller will estimate the date of shipment as closely as possible and will make every effort to ship as promised but cannot and does not guarantee shipping dates. All materials sent out will be carefully examined, counted and packed. The cost of any special packing or special handling caused by Buyer's requirements or requests shall be added to the amount of the order. No claim for shortages will be allowed unless made in writing within ten (10) days of receipt of a shipment. Claims for goods damaged or lost in transit should be made on the carrier, as Seller's responsibility ceases on delivery to the carrier.

PRODUCT RETURNS:

In keeping with its goal of Customer satisfaction with its products, Seller agrees to supply replacement products or credit for returned goods, subject to the following return policy and procedures. Returns must be authorized in writing (Material Return Authorization Form), and will be replaced or credited, at Seller's sole discretion, subject to the articles below.

(a) DEFECTIVE GOODS / WARRANTY. Seller warrants for one year from the date of shipment its manufactured products to the extent that it will replace those having defects in material or workmanship when used for the purpose which Seller recommends. If Seller's examination discloses to its satisfaction that the products are defective, and an adjustment is required, the amount of such adjustment shall be the net sales price of the defective products only and no allowance will be made for labor or expense of repairing defective products or damage resulting from the same. Seller warrants the products which it sells of other manufacturers to the extent of the warranties of the respective makers. **THIS IS SELLER'S SOLE WARRANTY. SELLER MAKES NO OTHER WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WHICH EXCEED THE OBLIGATION STATED HEREIN ARE HEREBY DISCLAIMED BY SELLER AND EXCLUDED FROM THE WARRANTY.** Seller neither assumes, nor authorizes any person to assume for it, any other obligation in connection with the sales of its products. This warranty shall not apply to any products or parts of products which (i) have been repaired or altered outside of Seller's factory, in any manner; or (ii) have been subjected to misuse, negligence or accident; or (iii) have been used in a manner contrary to Seller's instructions or recommendations.

(b) NON-DEFECTIVE GOODS. If Seller determines that current business conditions permit, Seller will take return of non-defective goods, up to 10% of each line item in the purchasing contract, if request is made within 120 days of original shipment. Upon authorization, goods must, on arrival at the Seller's factory, be found to be of current design, unaltered, and in first-class saleable condition. A handling charge of 25%, or amount agreed to in the purchasing contract, whichever is greater, will be deducted from credit memoranda. If goods are found not to be in saleable condition, the cost of upgrading to saleable condition plus the handling charge will be deducted from credit memoranda; or, at Seller's sole discretion, goods may be returned to the Buyer with transportation costs at Buyer's expense.

(c) TRANSPORTATION CHARGES. Returned goods must arrive at the Seller's factory via common carrier or normal ground delivery service with transportation charges prepaid, FOB the Seller's factory. Goods appearing to have been damaged in transit will not be received. Transportation charges for defective goods or items shipped by Seller in error will be credited back to the Buyer.

PRODUCT MODIFICATIONS:

Consistent with Seller's policy of offering quality products with optimum mechanical function, Seller reserves the right to modify any product contained herein without any prior notice. Seller also reserves the right to deliver modified products in fulfillment of any accepted order unless Buyer indicates otherwise.

COLLECTION CHARGES:

In the event Seller incurs any expenses for collection of an overdue account, reasonable collection charges including reasonable attorney's fees will be added to the balance due, and Buyer agrees to pay said charges.

TAXES:

The amount of any sales, excise or other taxes, if any, applicable to the products covered by this order, shall be added to the purchase price and shall be paid by Buyer unless Buyer provides Seller with an exemption certificate acceptable to the taxing authorities.

LABOR LAW:

All goods herein are manufactured in accordance with Fair Labor Standards Act of 1939 as amended.

Valex Corporate Offices & Manufacturing

6080 Leland Street
Ventura, California 93003
United States of America
805.658.0944
805.658.1376 FAX

2B – 2L Eyon-Hansan Industrial Park
Chungbuk-myon, Pyongtaek-city
Kyonggi Province, Korea
86-31-683-0119
82-31-683-7114 FAX

www.valex.com

